

S E T T O R E

laboratorio

laboratory  
balances



LABORATORY ELECTRONIC BALANCES & OENOLOGICAL EQUIPMENTS

ISO 9002



Carl Lidén Vågservice  
Huskvarnavägen 40  
554 54 Jönköping

Tel: 036-12 57 80  
Fax: 036-12 57 89

sales@carlliden.com  
<http://www.carlliden.com>

- Capacity: 150 g
- Accuracy: 0,1 mg
- Tare range (by subtraction): 150 g
- Linearity:  $\pm 0,2$  mg
- Stabilization time: 5 sec
- Operating temperature: 15°C - 35°C
- Pan diam.: 80 mm
- Full scale automatic calibration with internal calibration mass
- Bar-graph: indicator of the remaining capacity of the balance even after the zero taring over the whole range
- Data interface: RS232 I/O baud rate and parity adjustable
- Facility for weighing underneath the balance
- Membrane keyboard, solvent proof and easy to use with TARE, ON/OFF, CAL, PRINT keys
- 7 segments display, small decimal digits
- Indication of the reached stable weight
- External power supply: 220 V (-15%/+10%), 50 Hz (optional, 110V 60 Hz)
- Power consumption: 15 VA
- Total dimensions: 200 x 430 x 300 mm (W x D x H)
- Weighing chamber dimensions: 190 x 120 x 260 mm (W x D x H)

**Carl Lidén Vågservice**  
Huskvarnavägen 40  
554 54 Jönköping

Tel: 036-12 57 80  
Fax: 036-12 57 89

[sales@carlliden.com](mailto:sales@carlliden.com)  
<http://www.carlliden.com>