

Standard

CAL Adjusting programme CAL for quick setting of the balance's accuracy. External test weights additional price.

IP 54 Spray and dust protection: protection class is indicated in the symbol.

AKU Accu supply: rechargeable set.

230 V Mains adapter: 230 V / 50 Hz. Standard type D, on demand also available in type UK, AUS or USA.



Crane Balance HUS
With remote control

Back lighting
of the display standard

Adjusting programme CAL
guarantees high accuracy

Internal accu
standard, service life approx. 120 h

Charge display
visual via LED

Data hold function
The display is "frozen" via the HOLD key until any key is pressed again

W x D x H
Casing 150 x 140 x 150 mm, Total length from eye to hook 350 mm



Remote control
Infrared, range approx. 2.5 m. All functions can be selected

W x D x H
120 x 60 x 15 mm

Ready for use
Batteries size AA (2 x 1.5 V) inclusive

Model	Read-out d	Weighing range Max kg
KERN	g	
HUS 60 K 20	20	60
HUS 150 K 50	50	150
HUS 300 K 100	100	300
HUS 600 K 200	200	600

Net weight approx. 4 kg. LCD display with digit height 23 mm.

Hook
stainless steel, turnable



DKD Calibration Certificates

DKD = German Calibration Service

KERN issues in its own accredited laboratories internationally valid DKD Calibration Certificates ...

- for balances
- for test weights

KERN is a manufacturer of test weights in all OIML classes of accuracy E₁, E₂, F₁, F₂, M₁-M₃, from 1 mg to 2000 kg

KERN - Your DKD Calibration Partner

Carl Lidén Vågservice
Huskvarnavägen 40
554 54 Jönköping

Tfn: 036-125780
Fax: 036-125789

E-post: info@carlliden.com
Web: www.carlliden.com

